

© EPODOC / EPO

PN - HU40316/A2, 19861228

TI - METHOD FOR PRODUCING ARTIFICIAL SOLE LEATHER BASED ON LEATHER FIBRE

AB - Dry chrome tanned leather upper trimmings and similar waste is cut into 0.5-1 cm² pieces and rendered fibrous. Fibres are of 1.0-1.5 cm. length and 0.2-0.4 mm. width, 15-40 wt.% co- or terpolymer thermoplastic binder is added, the mixt. is heated to render it pliable and bond the fibres. This is followed by compression at 300-400 kg/cm² to form blocks. A further 10 wt.% (based on fibre wt. of colourant binder is applied by a spreading roller. This is followed by surface heat treatment and formation of a pattern, imitating natural leather soles.

PA - NADEX NADGAZDASAGI KUELKERESKE

IN - SALY GYOERGY

AP - HU19850000359 19850131

PR - HU19850000359 19850131

DT - I

© WPI / Thomson

AN - 1987-024105 [04]

TI - Synthetic sole material - contains fibres of waste chrome tanned leather and thermoplastic binder

AB - Dry chrome tanned leather upper trimmings and similar waste is cut into 0.5-1 cm² pieces and rendered fibrous. Fibres are of 1.0-1.5 cm. length and 0.2-0.4 mm. width, 15-40 wt.% co- or terpolymer thermoplastic binder is added, the mixt. is heated to render it pliable and bond the fibres. This is followed by compression at 300-400 kg/cm² to form blocks. A further 10 wt.% (based on fibre wt. of colourant binder is applied by a spreading roller. This is followed by surface heat treatment and formation of a pattern, imitating natural leather soles.

IW - SYNTHETIC SOLE MATERIAL CONTAIN FIBRE WASTE CHROME TAN LEATHER
THERMOPLASTIC BIND

PN - HU40316 A 19861228 DW198704

IC - A43B13/02; B29C65/44; D06N3/00

MC - A08-R A11-B09A A12-C04 D07-A D07-B F01-D10 F03-D F04-C05

DC - A82 A83 D18 F08

○ - P22

PA - (NADE-N) NADEX NADGAZDASAGI

IN - SALY G

AP - HU19850000359 19850131

PR - HU19850000359 19850131